SA-200

Altitude preselector uses barometric adjustment data from a digital encoding altimeter for extremely accurate altitude capture

The most important thing we build is trust





۲

۲

۲

MUTE

۲



Altitude preselector uses barometric adjustment data from a digital encoding altimeter for extremely accurate altitude capture

SA-200

The SA-200 Altitude Pre-Selector is a user friendly system that allows the pilot to pre-select the altitude target and uses the barometric adjustment data from a digital encoding altimeter for extremely accurate altitude capture.

The SA-200 Altitude Pre-Selector enables the pilot to preselect altitude. In addition, the pilot will receive both aural (tone and voice) and visual (LED) alert indications relative to the selected altitude.

The Altitude Selector/Alerter is a single, panelmounted unit that contains the display, the operating switches, and the computer. The system interfaces with encoding altimeters that provide a standard 100 ft. increment altitude

output and baro adjustment output. The unit also works with encoding altimeters that output baro corrected altitude via an RS-422 digital interface or EFIS system. Operation of the Altitude Selector/Alerter with a Cobahm autopilot is easy and straightforward.



System Fifty Five X Programmer Computer

• Voice and visual annunciations

- Alerts if aircraft departs selected altitude • Automatic vertical speed reduction prior to altitude capture
- Barometric adjustable, encoding altimeter

For further information please contact:

Cobham Avionics, Integrated Systems One S-TEC Way Municipal Airport Mineral Wells, TX 76067 USA Tel: (800) 872-7832 (817) 215-7600 Fax: (940) 325-3904 Email: info@s-tec.com

P/N 86298

()

۲